

SOUDALACK

Date: 17/05/2010**Page 1 of 1****Technical Characteristics:**

Base	Polyurethane
Consistency	Liquid
Curing System	Moisture curing
Specific Gravity	1,21 g/ml
Temperature resistance	-20°C till 80°C
Water absorption	None
Consumption	Ca. 6 m ² / L (for 2 layers)

Product:

Soudalack is a ready-to-use shiny polyurethane lacker.

Characteristics:

- High abrasion resistance
- High chemical resistance
- Resistant against oil and grease
- Very easy maintenance

Applications:

Paint and protect industrial flooring.
Treatment of garage and service station floors

Packaging:

Colours: red
Packaging: 20L drum

Shelflife:

12 months in unopened packaging in a cool and dry place at temperatures between +5°C and +25°C.

Substrates:

Nature: concrete
State: clean, dry and free of dust and grease
Preliminary treatment: porous substrates should be treated with a first diluted layer Soudalack + 20% white spirit.
We recommend a preliminary adhesion test on every substrate

Application:

Method: clean the floor carefully, making sure it is dry and grease free. Apply with brush or roller. Apply second layer crosswise over the first layer with a min. of 4 and max. of 24 hours interval.
Application temperature: +5°C to +25°C
Cleaning: with white spirit
Repair with: Soudalack

Health and Safety Recommendation:

Apply the usual industrial hygiene.

Remarks:

When painting polished concrete floors a careful pretreatment is necessary.
Brush the floor with a 15% hydrochloric acid solution and leave to work for at least 15 min.
Clean with high pressure cleaner. After drying, the primer layer and subsequent layers can be applied.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications, which are out of our control, we cannot accept any responsibility for the results obtained. In every case, it is recommended to carry out preliminary experiments